


EVOX 30 - F1 - L1

Bright

Dati Tecnici - Technical Data - Donnes Techniques - Datos Tecnicos



Italy	UK	France	Spain
Carrozzeria	Bodywork	Carrosserie	Carrocería
Dimensioni	Size	Dimensions	Medidas
Dimensioni camera a vuoto	Chamber size	Chambre à vide	Cámara de vacío
Volume vasca	Chamber volume	Volume de la chambre	Volumen de la cámara
Peso	Weight	Poids	Peso
Tensione	Power grid voltage	Voltage	Tensión
Potenza max assorbita	Max power absorption	Puissance max absorbée	Potencia máx
Pompa a vuoto	Vacuum pump	Pompe à vide	Bomba de vacío
Pressione finale	Final pressure	Pression finale	Presión final
Dimensione max busta	Max bag size	Dimension max du sac	Tamaño máx de bolsa

8MC/H
acciaio inox - stainless steel
495x600x288h mm
355x365x184h mm
17,10 lt.
29 kg
230V 50Hz
350 W
8 m ³ /h
2 mbar
300x400mm

12MC/H - F1 - L1
acciaio inox - stainless steel
495x600x288h mm
355x365x184h mm
17,10 lt.
35 kg
230V 50Hz
450 W
12 m ³ /h
2 mbar
300x400mm

Optional

Italy Ripiano inclinato per liquidi

UK Inclined shelf

France Plain incline

Spain Balda inclinado

Standard Optional Non disponibile

* non è possibile avere questi 2 optional assieme
 * please note, if you have the cut of seal you cannot have the double resistance.
 * Sur les machines à cloche, il n'est pas possible d'avoir simultanément le coupe sachet et la double résistance.
 * no se podrá contar con estos 2 opcionales juntos